



Intermat 9944


Fast-assembly hinge

Opening angle 125°



Concealed hinges, snap-on assembly, integrated door overlay and eccentric depth adjustment
 Opening angle 125°, cup diameter 35 mm
 Interimat 9944 hinges are snapped on to the mounting plate
 Depth adjustment via eccentric screw -0,5 mm/-3,5 mm
 Height adjustment via mounting plate +2 mm/-2 mm
 Overlay adjustment +0,5 mm/-3 mm

Door protrusion T for 0 mm distance and 3 mm cup distance



Mounting plates page 57-60
 Cover caps, accessories page 61
 For more technical information refer to page 32-36


Minimum reveal

Cup distance C mm	Door thickness mm				
	16	17	18	19	20
3	1,3	1,6	1,9	2,3	2,8
4	1,3	1,6	1,9	2,3	2,7
4,5	1,2	1,5	1,8	2,2	2,6
5	1,2	1,5	1,8	2,1	2,6


Mounting option	H mm	T mm
Full overlay	18,5	8
Half overlay	28	17,5

Cabinet construction

Face Frame



Frameless





Full overlay	PU 200	Door buffer Silent System (grey)		
		clip-on	screw-on	drill-in
TB 42 (screw-on)	1 070 715	9 015 112	9 015 115	9 013 069
TB 43 (press-in)	1 058 549			
TB FIX (toolless)	1 063 461	PU: 400	PU: 400	PU: 800

D	Overlay mm			
0	16	17	17,5	18
1,5	14,5	15,5	16	16,5
3	13	14	14,5	15
5	11	12	12,5	13
8	8	9	9,5	10
	3	4	4,5	5

Cup distance C mm

Mounting plate distances (D):
 Face frame: 0 mm; 4,5 mm
 Frameless: 0 mm; 1,5 mm; 3 mm; 5 mm; 8 mm



Half overlay	PU 200	Door buffer Silent System (grey)		
		clip-on	screw-on	drill-in
TB 42 (screw-on)	9 046 809	9 038 342	9 015 115	9 013 069
TB 43 (press-in)	1 058 550			
TB FIX (toolless)	1 063 463	PU: 400	PU: 400	PU: 800

D	Overlay mm			
1,5	5	6	6,5	7
	3	4	4,5	5

Cup distance C mm

D	Reveal mm				Side
	3	9	7	6	
3	12	10	9	8	19
	3	4	4,5	5	

Cup distance C mm