

KA 555

1" over extension ball bearing slide



- KA 555 ball bearing slide with 1/2" [12.7 mm] installation width, screw-on assembly, in 8 lengths
- Load capacity 150 lbs. [70 kg]
- Smooth progressive action with 1" [25.4 mm] over extension
- Precision steel ball bearings offer high lateral stability
- For drawer lengths 14" to 28" [356 to 711 mm]
- Handed slides, non-handed rail mount disconnect
- Cushioned in-and-out stops and positive hold-in detent
- Zinc plated and clear chromate finish
(Optional black E-Coat over zinc plated and clear chromate)

Item	Nominal length		Order no. 01-DP Packing (1pair per polybag)	PU pair	Order no. 02-Bulk Packing	PU pair	Drawer Box Length		Min. Cabinet Depth	
	mm	in					mm	in	mm	in
KA 555	350	14	00555-014-01500	5	00555-014-02500	5	355.6	14	362	14 1/4
KA 555	400	16	00555-016-01500	5	00555-016-02500	5	406.4	16	413	16 1/4
KA 555	450	18	00555-018-01500	5	00555-018-02500	5	457.2	18	464	18 1/4
KA 555	500	20	00555-020-01500	5	00555-020-02500	5	508.0	20	515	20 1/4
KA 555	550	22	00555-022-01500	5	00555-022-02500	5	558.8	22	565	22 1/4
KA 555	600	24	00555-024-01500	5	00555-024-02500	5	609.6	24	616	24 1/4
KA 555	650	26	00555-026-01500	5	00555-026-02500	5	660.4	26	667	26 1/4
KA 555	700	28	00555-028-01500	5	00555-028-02500	5	711.2	28	718	28 1/4

Finish: Standard – zinc plated and clear chromate; Special order – black E-Coat over zinc plated and clear chromate (call for information)

KA 555

1" over extension ball bearing slide

SLIDE SIZE		14	16	18	20	22	24	26	28	TOL	
SLIDE LENGTH	INCH	13.78	15.72	17.72	19.69	21.65	23.62	25.59	27.56	±.020	
	MM	350	400	450	500	550	600	650	700	±.5	
TRAVEL	INCH	14.78	16.72	18.72	20.69	22.65	24.62	26.59	28.56	±.125	
	MM	375	425	475	526	575	625	675	725	+6-3	
CHANNEL MOUNTING HOLES	A	INCH	6.30	7.56	8.82	10.08	11.34	12.60	13.86	15.12	±.020
		MM	160.0	192.0	224.0	256.0	288.0	320.0	352.0	384.0	±.5
	B	INCH	10.08	12.60	13.86	16.38	19.21	20.16	21.42	23.94	±.020
		MM	256.0	320.0	352.0	416.0	488.0	512.0	544.0	608.0	±.5
RAIL	C	INCH	12.62	14.59	16.59	18.60	20.61	22.62	24.52	26.59	±.020
		MM	320.5	370.5	421.5	472.5	523.5	574.5	624.5	675.5	±.5

